

# 4K/Ultra-HD Commercial Monitors



## DK40N

### Panel Attributes


Screen Size (Diag.)	40"
Panel Technology	Commercial-grade VA LED-LCD
Native Resolution	3840 x 2160
Pixel Pitch (mm)	0.2247(H) x 0.2247(V)
Brightness (Typ.)	500nit
Contrast Ratio (Typ.)	5,000:1
Displayable Colors	1.07 billion (10bit)
Viewing Angle	178° / 178°
Response Time (Typ. GTG)	8.5ms
Aspect Ratio	16:9

### Dimensions, Power & Other

Dimensions & Weight	34.45 x 20.3 x 2.04(in.); 50lbs
Mounting Pattern (mm)	300 x 200
Built-in Speaker	10W x 2
Electrical Ratings	AC 100 - 240V (50/60Hz)
Power Consumption (Typ.)	90W
Operating Temperature	32°F - 122°F
Operating Humidity Range	20~90% , Non-condensing
Industrial Reliability	50,000+Hours
Warranty	Two years (parts & labor)

### Connectivity

HDMI (input)	3 (3840x2160 @60Hz)
DisplayPort (Input)	2 (3840x2160 @60Hz)
DisplayPort (Output)	1 (3840x2160 @60Hz)
RS232C (Input)	1
RS232C (Output)	1
Audio Out (3.5mm)	1



### Sleek, Unbranded Housing

All GPO Display Commercial LCD monitors feature clean, unbranded black metal housing. Customized housing (front bezel/rear cover) is also available. Custom colors, logos and other designs are possible and allow you to match the interior design of a particular room or to match university or corporate colors.



### Ideal for Secure Applications

All GPO Display Commercial LCD monitors feature no Near-Field Communications, WiFi, or network connectivity of any kind. Only the minimum non-volatile memory required to operate an LCD is included. This makes this series of displays ideal for applications in secure environments.

- ✓ Commercial-grade 4K LED-LCD Panel
- ✓ Auto-Cooling System
- ✓ Tempered Glass (Optional)
- ✓ Clean metal (EGI) bezel (unbranded- custom logos available upon request)
- ✓ Anti-Glare (AG) Protective Glass (Optional)


\* GPO Display may change specifications and designs without notice.

# Mechanical Drawing


DK40N

GPO Display's Commercial-Grade 40" 4k LED LCD Monitors boast 3840x2160 native resolution for unparalleled clarity. [DK40N](#) features five video inputs supporting a 4K/UHD (3840x2160) signal. As with all DK-series models from GPO Display, this model is rated for 24/7 use. Custom housing colors & logos are available upon request.

## FRONT VIEW



## REAR VIEW



Product specification and design are subject to change without notice.

Copyright 2019 GPO Display All rights reserved. This document may not be copied in any form without written permission from GPO Display Rev. 030719-01