

# Comparison of GPO Display LCD Video Wall Series



## Display Specifications

Series Name	Self-Monitoring	New Standard	Easy-4K	Sturdiglass
Available Screen Sizes	46" / 49" / 55" / 75"	46" / 49" / 55"	46" / 49" / 55"	46" / 49" / 55"
Available Brightness	400 / 500 / 700nit	500 / 700nit	500 / 700nit	500 / 700nit
4K daisy-chain support	-	-	✓	✓
Optically-bonded protective glass	-	✓	-	✓
Combined Bezel Width	1.7-3.5mm, 23mm	1.7-3.5mm, 11.8mm	1.7-1.8mm, 3.5mm	1.7-1.8mm, 3.5mm

## Other

Built-in Video Wall Processor	✓	✓	✓	✓
24/7/365 Rated	✓	✓	✓	✓
Portrait/Landscape compatible	✓	✓	✓	✓
Auto-Cooling System	✓	-	-	-
Overheating Prevention	-	✓	✓	✓

## Inputs/Outputs

DVI	2in/2out	1in/1out	-	-
VGA	1in/1out	1in/1out	-	-
RS232C	1in/1out	1in/1out	1in/1out	1in/1out
HDMI	-	1in	1in/1out (3840x2160)	1in/1out (3840x2160)
DisplayPort	-	1in	1in	1in
HD-SDI	-	-	Optional in&out	Optional in&out
LAN	1in (ACR Only)	1in (ACR Lite only)	1in (control)	1in (control)

## GPO Display Features

Display Monitoring/Diagnostics	<b>Auto-Condition Reporting</b>	<b>ACR Lite</b>	WallExpress (Basic)	WallExpress (Basic)
Color Temperature Presets	-	-	✓	✓
Touch	-	-	-	Optional: 6pt, 12pt, or 32pt IR
Warranty	Cover 3/Quick 3*	3yrs (parts & labor)	Cover 3/Quick 3*	3yrs (parts & labor)

\*Three years (parts & labor) with courtesy advance replacement service