

Signage Player



ARM100

Our Signage Players feature silent, fanless operation along with powerful server software. This allows for network updating of large, multi-screen deployments via single, or multiple operators. These players also support up to 4K (3840×2160) content, and are the perfect complement to all of our displays.

Model ARM100

SYSTEM

CPU	ARM
RAM	2GB
Storage	32GB
Operating System	Android 4.4
Network Interface	10/ 100/ 1000Mb BaseT LAN; Wi-Fi (optional)
Display Resolution	Up to 3840 x 2160 @ 60Hz
Video Resolution	3840 x 2160

Dimensions, Power & Other

CMS(Content Management Software)	Included
FAN	Fanless
Dimensions (H x W x D)	1.4 x 5.5 x 5.1in
Weight	0.88lbs
Temperature	Operation: 32°F – 104°F
Humidity	0% – 90%
AC/DC Adapter	IN:100-240VAC, Out:12V DC
Mounting Bracket	Included

Connectivity

Display Connectors	1 x HDMI
Audio Jack	3.5mm phone jack x 5/ Digital output x 1
USB Port	USB 2.0
Power	DC x 1
LAN	RJ45 for Ethernet x 1



Image

- JPEG (.jpg, .jpeg) • GIF (.gif)
- BMP (.bmp) • PNG (.png)

Audio

- MP3 (.mp3) •
- Windows Media Audio (.wma)
- MP4 (.mp4)

Video

- MP4 (.mp4) (de-interlaced only)
- Flash Video (.flv) (de-interlaced/progressive only)
- MPEG1/2 (.mpe, .mpg, .mpeg) (de-interlaced/progressive only)
- 3GP Video(.3gp)(de-interlaced/progressive only)
- AVI (.avi) (de-interlaced only)
- DVD Video (.vob) (de-interlaced only)
- Apple QuickTime (.mov) (de-interlaced/progressive only)
- HTML (.html, .htm) (Internet Explorer support required)

Others

HTML 5 Widget

- ✓ Support up to 4K(3840x2160@60Hz)
- ✓ Android 4.4 operating system
- ✓ Robust, Compact & Energy-efficient Digital Signage
- ✓ Support for multiple window of content
- ✓ Real-time or scheduled content playback
- ✓ Automatic content download recovery



* GPO Display may change specifications and designs without notice.