

# TS55KP10



## Touch Screen

### Commercial Monitor

This premium line of PCAP touch screens delivers on both performance and appearance. Each model can be configured upon request to fit into wall pockets, tables, or other fixtures.



# Highlights

TS55KP10

Customizable housing.



10pt projected capacitive (PCAP) touch.




"Secure-Ready" = No NFC, RF, WiFi, or embedded computing.



24/7-rated.



Video wall-capable (DP output and video wall mode).



# Specifications

## Panel Attributes

Panel Technology	Commercial-grade IPS LED-LCD
Surface Treatment	Hard coating (2H), Anti-glare treatment of the front polarizer (Haze 28% typ.)
Screen Size (diag.)	55"
Native Resolution	3840 x 2160
Active Area (mm)	1209.6 x 680.4
Brightness (typ.)	500nit
Contrast Ratio (typ.)	1,100:1
Displayable Colors	10bit(D), 1.07 Billion colors
Viewing Angle	178°/ 178°
Aspect Ratio	16:9
Refresh Rate	60Hz

## Dimensions, Power & Other

Display Dimensions (W x H x D) + Weight	50.47 x 29.94 x 2.64 (in) - 88lbs
Packed Dimensions (W x H x D) + Weight	54.72 x 36.22 x 9.84 (in) - 97lbs
Display Orientation	Landscape or Portrait
Heat Output (BTU/hr)	443
Mounting Pattern (mm)	400 x 300
Electrical Ratings	AC 100 - 240V (50/60Hz)
Power Consumption (typ.)	130W
Standby Power Consumption	<1W
Operating Temperature	32°F - 122°F
Operating Humidity Range	10~90%
Industrial Reliability	50,000+ Hours
Usage Ratings (hrs/days)	24/7**
Warranty	Two Years (parts & labor)

\*\*Consult with GPO Display regarding best practices for preventing image retention and for prolonging display lifetime.

# Specifications

## Touch Specification

Technology	Projected Capacitive Touch
Glass	5mm Tempered Glass
Simultaneous Touch Points	10 pt
Touch Accuracy	2mm
Response Time	16ms
Interface	USB 2.0, HID-Compliant, Plug & Play
Supported OS	Windows / Android / Mac* / Linux (1pt)
Detection Method	Finger, gloved hand or any other pointer
Min. Touch Object Size	9mm

\*Drivers may be required for Mac OS. Contact GPO Display for more information.

## Connectivity

HDMI	3 x Input
DisplayPort	2 x Input, 1 x Output
RS-232	1 x Input, 1 x Output
AC Power Inlet	1
Audio	1 x 3.5mm Out, Built-in Speaker 10W x 2

### Accessories:

- RS-232 cable x1
- DP cable x1
- AC power cord x1
- Remote control x1
- Batteries for remote control

### Includes:


- Serial control software

### Options:

- Custom logos
- Custom housing colors
- Anti-Glare protective glass
- Tempered glass

# Drawings

## Front View



## Rear View

