

Signage Player



ARM100

Our Signage Players feature silent, fanless operation along with powerful server software. This allows for network updating of large, multi-screen deployments via single, or multiple operators. These players also support up to 4K (3840x2160) content, and are the perfect complement to all of our displays.

Model		ARM100
SYSTEM		
CPU	ARM	
RAM	2GB	
Storage	32GB	
Operating System	Android 4.4	
Network Interface	10/ 100/ 1000Mb BaseT LAN; Wi-Fi (optional)	
Display Resolution	Up to 3840 x 2160 @ 60Hz	
Video Resolution	3840 x 2160	



Dimensions, Power & Other	
CMS(Content Management Software)	Included
FAN	Fanless
Dimensions (H x W x D)	1.4 x 5.5 x 5.1in
Weight	0.88lbs
Temperature	Operation: 32°F – 104°F
Humidity	0% – 90%
AC/DC Adapter	IN:100-240VAC, Out:12V DC
Mounting Bracket	Included

Connectivity	
Display Connectors	1 x HDMI
Audio Jack	3.5mm phone jack x 5/ Digital output x 1
USB Port	USB 2.0
Power	DC x 1
LAN	RJ45 for Ethernet x 1

Image

- JPEG (.jpg, .jpeg) • GIF (.gif)
- BMP (.bmp) • PNG (.png)

Audio

- MP3 (.mp3) •
- Windows Media Audio (.wma)
- MP4 (.mp4)

Video

- MP4 (.mp4) (de-interlaced only)
- Flash Video (.flv) (de-interlaced/progressive only)
- MPEG1/2 (.mpe, .mpg, .mpeg) (de-interlaced/progressive only)
- 3GP Video(.3gp)(de-interlaced/progressive only)
- AVI (.avi) (de-interlaced only)
- DVD Video (.vob) (de-interlaced only)
- Apple QuickTime (.mov) (de-interlaced/progressive only)
- HTML (.html, .htm) (Internet Explorer support required)

Others

HTML 5 Widget

- ✓ Support up to 4K(3840x2160@60Hz)
- ✓ Android 4.4 operating system
- ✓ Robust, Compact & Energy-efficient Digital Signage
- ✓ Support for multiple window of content
- ✓ Real-time or scheduled content playback
- ✓ Automatic content download recovery



* GPO Display may change specifications and designs without notice.