



Visual solutions created for *you*

NEX55MLU



LCD Video Wall

The Next Generation


Our NEX-Series LCD Video Walls provide superior connectivity, improved daisy-chain capabilities, and a wide range of bezel and brightness options for the most demanding applications.




Highlights

NEX55MLU

Ultra Narrow Bezel (UNB) with a tiled gap of 3.5mm.




Extended daisy-chaining of 4K/60Hz video signals in arrays up to 5 wide x 5 high.




“Secure-Ready” = No NFC, RF, WiFi, or embedded computing.




Able to define a “master set” for control of all displays using a single IR remote controller.



On/Off Scheduler (no separate control system required).



Quick presets that allow you to recall source layouts with a single serial command.



Panel Attributes


Panel Technology	Commercial-grade IPS / Direct-LED back light
Bezel Width	UNB 3.5 mm (combined)
Surface Treatment	Hard Coating (3H), Anti-glare treatment of front polarizer (Haze 28%)
Screen Size (diag.)	55"
Native Resolution	1920 x 1080
Active Area (mm)	1209.6 x 680.4
Brightness (typ.)	500nit
Contrast Ratio (typ.) / DCR	1,400:1 / 500,000:1
Displayable Colors	10bit(D), 1.07 Billion colors
Viewing Angle	178° / 178°
Aspect Ratio	16:9
Refresh Rate	60Hz

Includes:

- Video wall control software
- Built-in video wall processor (up to 11 x 11 Natural Mode)
- Direct connection to technical support team

Options:

- Auto-aligning H-mount (includes side covers)
- Top & bottom covers
- Trim for use with third party mounts
- IR extender



Dimensions, Power & Other

Display Dimensions (W x D x H) + Weight	47.77 x 3.39 x 26.94 (in) - 62lbs
Packed Dimensions (W x D x H) + Weight	54.5 x 9.5 x 33.5 (in) - 79lbs
Display Orientation	Landscape or Portrait
Heat Output (BTU/hr)	529
Mounting Pattern (mm)	600 x 400
Electrical Ratings	AC 100 - 240V (50/60Hz)
Power Consumption (typ.)	155W
Standby Power Consumption	<1W
Operating Temperature	32°F -104°F
Operating Humidity Range	10~90%
Industrial Reliability	60,000+ Hours
Usage Ratings (hrs/days)	24/7**
Warranty	Three Years (cover 3/ quick 3)

****Consult with GPO Display regarding best practices for preventing image retention and for prolonging display lifetime.**


Connectivity

Display Port	2 x Input, 1 x Output (<i>can carry any input signal</i>)
HDMI (up to 3840 x 2160)	3 x Input
RS-232	1 x Input, 1 x Output
Ethernet (RJ45 for control & monitoring)	1 x Input
USB (for service only)	1 x Input
Audio (3.5mm jack)	1 x Output

Accessories:

- RS-232 cable x1
- DP cable x1
- AC power cord x1
- Remote control x1
- Batteries for remote control

Set Drawing



Set + H-Mount Drawing

