



Visual solutions created for *you*

PA27H



Panoramic LCD

Stretch Your Imagination

Featuring a distinctive, “stretched” aspect ratio, these displays fit in spaces which traditional 16:9 displays will not.

Menu boards, ad space and lobby signage all benefit from the eye-catching design.



Highlights

PA27H-P


Includes wall mount and trim (Top, Left, Right, Bottom).



Unique stretched aspect ratio.



Sleek, unbranded, black powder-coated metal housing.




“Secure-Ready” = No NFC, RF, WiFi, or embedded computing.



Available with both fixed and flexible EDID.



Ability to toggle the display area using a hotkey on remote.



Panel Attributes

Panel Technology	27" Stretched LED-LCD
Surface Treatment	Hard Coating (3H), anti-glare treatment
Screen Size (diag.)	27"
Native Resolution	1920 x 360
Active Area (mm)	698.4 x 131.0
Brightness (typ.)	700nit
Contrast Ratio (typ.)	5,000:1
Displayable Colors	1.07B (Dithered 10bit)
Viewing Angle	178°/ 178°
Aspect Ratio	16:3

Dimensions, Power & Other

Display Dimensions (W x H x D) + Weight	28.84 x 6.5 x 2.24 (in) - 10lbs
Packed Dimensions (W x H x D) + Weight	36 x 14 x 9 (in) - 21lbs
Display Orientation	Landscape or Portrait
Mounting Pattern (mm)	100 x 100
Electrical Ratings/ Power Type	AC 100 -240V (50/60Hz)/ Power Adapter 24V 2.5A 3pin
Power Consumption (typ.)	27W
Standby Power Consumption	<1W
Heat Output (BTU/hr)	92
Operating Temperature	32°F -104°F
Operating Humidity Range	20~80%
Industrial Reliability	60,000 + hours
Usage Ratings (hrs/days)	24/7**
Warranty	Three year advance replacement (Cover 3/ Quick 3)

****Consult with GPO Display regarding best practices for preventing image retention and for prolonging display lifetime.**

Connectivity

HDMI	2 x Input
VGA	1 x Input
RS-232	1 x Input
DisplayPort	1 x Input

Accessories:

- HDMI cable x1
- RS-232 cable x1
- Remote controller x1
- AAA batteries x2
- Power adapter x1
- Power cord x1
- Power adapter “brick” mounting bracket x1

Options:

- Custom housing
- Custom colors
- Custom logos
- Other designs
- Tempered protective glass

Technical drawing of a rectangular plate. The overall dimensions are 28.84 [732.5] mm in width and 6.5 [165.0] mm in height. The drawing shows a central rectangular area with two horizontal dimensions: 27.5 [698.4] mm and 27.57 [700.4] mm. The vertical dimensions on the left are 5.16 [131.0] mm and 5.23 [133.0] mm. The drawing is a top-down view of a rectangular plate with a central rectangular area defined by dashed lines. The overall width is 28.84 mm [732.5] and the overall height is 6.5 mm [165.0]. The central area has a width of 27.5 mm [698.4] and 27.57 mm [700.4], and a height of 5.16 mm [131.0] and 5.23 mm [133.0].

[illegible]