



Visual solutions created for *you*

PA28H



Panoramic LCD

Stretch Your Imagination

Featuring a distinctive, “stretched” aspect ratio, these displays fit in spaces which traditional 16:9 displays will not.

Menu boards, ad space and lobby signage all benefit from the eye-catching design.



Highlights

PA28H-P


Includes wall mount and trim (Top, Left, Right, Bottom).



Unique stretched aspect ratio.



Sleek, unbranded, black powder-coated metal housing.




“Secure-Ready” = No NFC, RF, WiFi, or embedded computing.



Available with both fixed and flexible EDID.



Ability to toggle the display area using a hotkey on remote.



Panel Attributes

Panel Technology	28" Stretched LED-LCD
Surface Treatment	Hard Coating (3H), anti-glare treatment
Screen Size (diag.)	28.5"
Native Resolution	1920 x 540
Active Area (mm)	698.4 x 196.4
Brightness (typ.)	700nit
Contrast Ratio (typ.)	5,000:1
Displayable Colors	1.07B (Dithered 10bit)
Viewing Angle	178°/ 178°
Aspect Ratio	32:9

Dimensions, Power & Other

Display Dimensions (W x H x D) + Weight	28.66 x 9.06 x 2.34 (in) - 16lbs
Packed Dimensions (W x H x D) + Weight	36 x 14 x 9 (in) - 24lbs
Display Orientation	Landscape or Portrait
Mounting Pattern (mm)	100 x 100
Electrical Ratings/ Power Type	AC 100 - 240V (50/60Hz)/ Power Adapter 24V 2.5A 3pin
Power Consumption (typ.)	36W
Standby Power Consumption	<1W
Heat Output (BTU/hr)	123
Operating Temperature	32°F - 104°F
Operating Humidity Range	20~80%
Industrial Reliability	60,000 + hours
Usage Ratings (hrs/days)	24/7**
Warranty	Three year advance replacement (Cover 3/ Quick 3)

****Consult with GPO Display regarding best practices for preventing image retention and for prolonging display lifetime.**

Connectivity

HDMI	2
VGA	1
RS-232	1
DC Input	1

Accessories:

- HDMI cable x1
- RS-232 cable x1
- Remote controller x1
- AAA batteries x2
- Power adapter x1
- Power cord x1
- Power adapter “brick” mounting bracket x1

Options:

- Custom housing
- Custom colors
- Custom logos
- Other designs
- Tempered protective glass

