



Visual solutions created for *you*

EM32SL



Departures			
Time	Destination	Flight	Check-in
05:40	Antalya	QU 4401	-
05:55	Antalya	QU 4403	-
06:00	Munich	LH 2547	-
06:00	Paris/CDG	AF 1653	-
06:00	Paris/CDG	DL 8519	-
06:00	Paris/CDG	PS 9283	-
06:00	Paris/CDG	KL 2285	-
06:10	Antalya	PS 5323	-
06:50	Sharm EL S	PS 5203	-
06:50	Frankfurt	LH 1493	-
07:00	Vienna	OS 0668	-
07:00	Vienna	PS 9814	-
09:20	Antalya	QU 4413	-
07:55	Burgas	PS 5093	-

PoE Monitor


Secure Line

GPO Display's Power Over Ethernet (PoE) Monitors are designed to deliver critical, detailed information in versatile environments where traditional power solutions are impractical. Additionally, the secure line option ensures enhanced security for sensitive information, while the Android SoC option provides robust, built-in processing power for seamless performance.



Highlights

EM32SL




POE Splitter

No need for a separate
POE splitter




AC Outlet

No AC outlet
required



12/24VDC Outlet

For third-party devices
such as media players



DisplayPort

DisplayPort output
for duplicating
images




Secure-Ready

No NFC, RF, WiFi,
Bluetooth or
embedded computing



24/7 Rated

For demanding
applications



Housing

Sleek, unbranded,
black powder-
coated metal

Panel Attributes

Panel Technology	Commercial-grade LED-LCD
Surface Treatment	Hard coating (3H), Anti-glare treatment (Haze 2%)
Screen Size (diag.)	32"
Native Resolution	1920 × 1080
Active Area (mm)	698.4 (H) × 392.85 (V)
Brightness (typ.)	500nit
Contrast Ratio (typ.)	4,000:1
Displayable Colors	16.7 Million colors, 8-bit
Viewing Angle	178° / 178°
Aspect Ratio	16:9
Refresh Rate	60Hz

Dimensions, Power & Other

Display Dimensions (W x H x D) + Weight	28.46 × 16.46 × 2.2 (in), 22 lbs
Packed Dimensions (W x H x D) + Weight	33 × 21.5 × 7.5 (in), 28.5 lbs
Display Orientation	Landscape or Portrait
Mounting Pattern (mm)	100 × 100, M6
Built in Speaker	Yes
Power Consumption (max.)	40W
Heat Output (BTU/hr)	136.5
Operating Temperature	32–104°F
Operating Humidity Range	20~90%
Industrial Reliability	50,000hrs+
Usage Ratings (hrs/days)	24/7
Warranty	Two Years (parts & labor)

****Consult with GPO Display regarding best practices for preventing image retention and for prolonging display lifetime.**

Connectivity & PoE Info

HDMI	1 × Input
DisplayPort	1 × Input, 1 × Output (video daisy-chain)
RS-232	1 × Input: 3-pin terminal block (3.5mm pitch)
PoE Input Port	1 × 10/100/1000 BASE-T RJ45
Data Output Port	1 × 10/100/1000 BASE-T RJ45
DC Plug Connector	2 × Input/Output, 1 × Output: 3-pin terminal block (5.08mm pitch)
Power Requirements	4-pair IEEE 802.3bt Type 4 PoE++ (90W+)
Power Output*	w/ 802.3 bt type 4 PoE++ input: 12V DC: 12W, 1A (max.) 24V DC: 19.2W, 0.8A (max.)
Standards Compliance	IEEE 802.3 10BASE-T Ethernet IEEE 802.3u 100BASE-TX Fast Ethernet IEEE 802.3ab 1000BASE-T Gigabit Ethernet IEEE 802.3bt 4-pair Power over Ethernet Type 4

**Notes: Power availability depends upon Power Source Equipment (PSE). Actual Amperage requirements of input device are often different from those listed on device's AC-DC adapter. The above figures assume power for a single external device.*

LED Status Indicators:

Green = Power On / Signal Detected

Red = Power Off

Amber = Standby / No Signal


Accessories:

- (1) Slim mount
- (1) HDMI cable
- (1) DC power cable
- (1) Remote controller
- (2) AAA batteries for remote control
- (1) 1m Ethernet cable

Options:

- Custom housing
- Custom colors
- Custom logos
- Other designs
- Tempered protective glass

Display Only



Display & Slim Mount

